

**Serie | 6, Island cooker hood, 90 cm,
Stainless steel
DIB98JQ50B**

A⁺



Optional accessories

DHZ1231 : Adapter for roof inclination left/right
 DHZ1241 : Adapter for roof inclination front/back
 DHZ1246 : Chimney extension 1100 mm
 DHZ1251 : Extension for mounting kit 500 mm
 DHZ1256 : Chimney extension 1600 mm
 DHZ5346 : Standard odor filter (replacement)
 DHZ5385 : Standard recirculation kit
 DIZ2CX5C6 : Clean Air Plus recirc. kit external
 DZZ0XX0P0 : Long Life odor filter (replacement)
 DZZ1XX1B6 : Clean Air Plus odor filter (replacement)

**Stylish island chimney hoods perfectly
complement island hob installations.**

- **PerfectAir sensor:** automatic control of settings for maximum extractor performance with minimal noise.
- **Grease filtration level:** filters out over 85% of the grease from kitchen air
- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **DirectSelect control:** direct selection of desired settings and light.
- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	698-878/698-998
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	30.677
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m3/h) :	445
Boost position output recirculating (m3/h) :	391.0
Maximum output recirculating air (m3/h) :	313
Boost position air extraction (m³/h) :	867
Number of lights (Stck) :	4
Noise level (dB(A) re 1 pW) :	54
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242005099276
Connection rating (W) :	166
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Island



4 242005 099276

Serie | 6, Island cooker hood, 90 cm, Stainless steel DIB98JQ50B

**Stylish island chimney hoods perfectly
complement island hob installations.**

Key performance features:

- Energy Efficiency Class:A+(at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use:445 m³/h
Intensive:867m³/h
- Noise max. Normal Level:Noise, max. speed in normal us: 54 dBdB*

Special features

- PerfectAir sensor
- TouchControlwithlightline
- 3 power levels and 2 intensive settings
- 4x1.5W LED light
- Colour Temperature:3500 K
- Dimmer function
- Efficient BLDC-technology
- Automatic intensive revert (6mins)
- Automatic after running (Automatic after running (10 min))
- 3 removable metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Additional noise reduction insulation
- easy to cleanInner frame

Design

- Island chimney hood
- Designed for ceiling mounted installation
- TouchControl
- Electronic control
- Efficient BLDC technology

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max.445m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air:54dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use:54 dB(A) re 1 pW
Intensive:69dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate:54dB (A) re 1pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use:353 m³/h
Intensive:457 m³/h
Noise level in recirculation mode:
Max. normal use:67 dB(A) re 1 pW
Intensive:71dB(A) re 1 pW
- Power rating:166 W
- Light Intensity:423lux
- Electrical cable length1.3 m
- Diameter pipe Ø150mm (Ø120mm enclosed)
- Dimensions exhaust air (HxWxD):744-924x898x600mm
- Dimensions recirculating (HxWxD):744-1044x898x600mm
- Dimensions recirculating with CleanAir module (HxWxD):812-1044x898x600mm
- Blower Efficiency Class:A*
- Lighting Efficiency Class:A*
- Grease Filtering Efficiency Class:B*
- Average Energy Consumption:31.6kWh/year*

Optional accessories

- Recirculating kitDHZ1231

** In accordance with the EU-Regulation No 65/2014*

Serie | 6, Island cooker hood, 90 cm, Stainless steel DIB98JQ50B

