# N 90, Induction hob, 90 cm, Black T50FS41X0





TwistPadFire®	Flex Induction	Power Move	Frying Sensor
(Ph		L A H	

#### Optional accessories

Stainless Steel roaster with glas lid		
Steaming Rack for Stainless Steel roaste		
Griddle Plate		
Teppan Yaki (large)		
Pan Ø 22 / 26 cm		
Pot Ø 14 (bottom) / 16 cm (top)		
Pot Ø 18 (bottom) / 20 cm (top)		
Set of 2 pots and 1 pan		

- $\sqrt{~}$  TwistPadFire® our removable, magnetic, illuminated control dial that gives you precise control over all cooking zones.
- $\sqrt{\rm Flex}$  Induction place your pots and pans within the flex zone anywhere you want and heat them exactly where they stand.
- $\sqrt{}$  Power Move the flex zone offers three heating zones: boiling in front, simmering in the middle and warming in the rear.
- $\checkmark\,$  Frying Sensor with 5 selectable temperature settings it monitors the set temperature and holds it steady.
- $\checkmark\,$  Power Boost optimized power level function for more flexible and even faster heating.

# Features

# Technical Data

Product name/family : Cooking zone ceramic Construction type : Built-in Energy input : Electric Total number of positions that can be used at the same time : 4 Required niche size for installation (HxWxD) :  $51 \times 880-880 \times$ 330-330 Width of the appliance : 903 Dimensions : 51 x 903 x 346 Dimensions of the packed product (HxWxD) (mm) :  $126 \times 1031 \times 472$ Net weight (kg) : 14.835 Gross weight (kg) : 16.0 Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic Color of surface : Black Approval certificates : AENOR, CE Length of electrical supply cord (cm) : 110 EAN code : 4242004195658 Electrical connection rating (W): 7400 Voltage (V) : 220-240 Frequency (Hz) : 50; 60



# N 90, Induction hob, 90 cm, Black T50FS41X0



#### Features

# Design

- 903 mm
- Bevelled front edge

## Control

- TwistPad® Fire
- Frying Sensor:5 frying levels

## Flexibility

- 2 Flex zones
- 4 zone induction hob
- PowerMove

## Special features

- Power Boost function for all zones
- PanBoost
- 17 stage 1,1.,2..9
- Digital display of cooking levels
- 2 stage residual heat indicators
- switch-off timer, all cook. z. LED timer for each zone with switch off function and acoustic signal Count up timer
- ReStart function
- pan recognition
  Safety cut out facility
  Control panel lock
  Control panel suspension
- yes
- Energy consumption display

#### Technical information

- Cooking zones: 1 x Ø210 mmx400 mm,3.3 KW(max. Power levels3.7 KW) Induction or 2 x Ø 190 mm,2.2 KW(max. Power levels3.7 KW) Induction; 1 x Ø210 mmx400 mm,3.3 KW(max. Power levels3.7 KW) Induction or 2 x Ø 190 mm,2.2 KW(max. Power levels3.7 KW) Induction
- Measurement: (H/B/T)51x903x346mm
- Installation dimensions: (ID/W/D)51 mmx880 mmx330 mm
- 90 cmwidth
- Length wire connection:110 cm
- Main switch
- Min. worktop thickness:16 mm
- Output7400 W
- Cable included in packaging

# N 90, Induction hob, 90 cm, Black T50FS41X0



