

iQ500, Canopy cooker hood, 70 cm, Stainless steel LB78574GB

C



The powerful canopy cooker hood is concealed in a unit above the hob.

- ✓ LED lights: For optimal visibility and ambience when cooking.
- ✓ For peak performance - Intensive setting with automatic revert

Features

Technical Data

Typology : Traditional
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 8.917
 Type of control : Electronic
 Maximum output air extraction (m3/h) : 630
 Boost position output recirculating (m3/h) : 310.0
 Maximum output recirculating air (m3/h) : 300
 Boost position air extraction (m³/h) : 730
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 66
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003686263
 Connection rating (W) : 277
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation type : Built-in

Optional accessories

LZ55750	Standard recirculation kit
LZ55651	Standard odor filter (replacement)
LZ11IXC16	Clean Air Plus recirc. kit external
LZ11IXB16	Clean Air Plus odor filter (replacement)
LZ11ITD11	Long Life recirculation kit external
LZ10ITP00	



iQ500, Canopy cooker hood, 70 cm, Stainless steel LB78574GB

Features

Key Information

- Soft touch button control for extractor speeds and light
- 3 x power levels plus intensive setting
- 6 min.
- 2 x 1W LED lights
- 2 x metal grease filter cassettes
- Steel filter cover, Steel filter cover
- Rim ventilation

Design

- 70 cm wide
- Stainless Steel
- For installation in a kitchen cabinet
- Electronic control via Soft touch button control
- White electronic display

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 \varnothing 15 cm:
 - max. Normal use 630 m³/h
 - Intensive 730 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 66 dB(A) re 1 pW
 - Intensive: 69 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode:
 - Max. normal use: 571 m³/h
 - Intensive: 664 m³/h
 - Noise level in recirculation mode:
 - Max. normal use: 72 dB(A) re 1 pW
 - Intensive: 75 dB(A) re 1 pW
- Power rating: 277 W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Dimensions (WxD): 700 x 300 mm
- built-in dimensions (HxWxD): 418 x 676 x 264 mm
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Average Energy Consumption: 104.2 kWh/year*
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*

* In accordance with the EU-Regulation No 65/2014

iQ500, Canopy cooker hood, 70 cm,
Stainless steel
LB78574GB

Dimensioned drawings

