

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94BBC50B



D



Box design extractor hood with high extraction rate.

✓ LED lights: For optimal visibility and ambience when cooking.

Features

Technical Data

Typology : Chimney
Approval certificates : CE, G-Mark, VDE
Length of electrical supply cord (cm) : 130
Height of the chimney (mm) : 583-912/583-1022
Height of product, without chimney (mm) : 53
Minimum distance above an electric hob : 550
Minimum distance above a gas hob : 650
Net weight (kg) : 12.524
Type of control : mechanical
Number of speed settings : 3
Maximum output air extraction (m3/h) : 365
Maximum output recirculating air (m3/h) : 195
Number of lights (Stck) : 2
Noise level (dB(A) re 1 pW) : 64
Diameter of air outlet (mm) : 120 / 150
Grease filter material : Washable aluminium
EAN code : 4242003811184
Connection rating (W) : 100
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 50; 60
Plug type : GB plug
Installation type : Wall-mounted



4 242003 811184

Optional accessories

LZ50961 : Backboard 90 x 72 cm , LZ50960 : Backboard 90x65cm , LZ31XXB16 : Clean Air Plus odor filter (replacement) , LZ12350 : Chimney extension 1500 mm , LZ12250 : Chimney extension 1000 mm , LZ11FXD51 : Long Life recirculation kit external , LZ11FXC56 : Clean Air Plus recirc. kit external , LZ11DXI16 : Clean Air Plus recirculation kit , LZ10FXJ00 : Long Life recirculation kit , LZ10DXU00 : Standard recirculation kit , LZ10DXA00 : Standard odor filter (replacement) , LZ00XXP00 : Long Life odor filter (replacement)

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94BBC50B

Features

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 365 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB*

Features

- Push button control for extractor speeds and light
- 3 x power levels
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- 3 x metal grease filter cassettes - dishwasher safe
- For wall mounted installation

Design

- Chimney hood
- Mechanical

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Maximum extraction rate exhaust air 365 m³/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW
- Power rating: 100 W
- Light Intensity: 91 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 635-1075 x 900 x 500 mm
-
- Dimensions recirculating with CleanAir module (HxWxD):
- 703 x 900 x 500 mm - mounting with outer chimney
- 833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 53.1 kWh/year*

Optional accessories

- Recirculating kit LZ00XP00

* In accordance with the EU-Regulation No 65/2014

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94BBC50B

Dimensioned drawings

