

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94PBC50B



D



Pyramid design extractor hood with a high extraction rate.

✓ LED lights: For optimal visibility and ambience when cooking.

Features

Technical Data

Typology : Chimney
Approval certificates : CE, VDE
Length of electrical supply cord (cm) : 130
Height of the chimney (mm) : 553-730/573-730
Height of product, without chimney (mm) : 246
Minimum distance above an electric hob : 550
Minimum distance above a gas hob : 650
Net weight (kg) : 10.686
Type of control : mechanical
Number of speed settings : 3
Maximum output air extraction (m3/h) : 365
Maximum output recirculating air (m3/h) : 213
Number of lights (Stck) : 2
Noise level (dB(A) re 1 pW) : 65
Diameter of air outlet (mm) : 120 / 150
Grease filter material : Washable aluminium
EAN code : 4242003801314
Connection rating (W) : 100
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 50; 60
Plug type : GB plug
Installation type : Wall-mounted



4 242003 801314

Optional accessories

LZ52751	Standard odor filter (replacement)
LZ52750	Standard recirculation kit
LZ50961	Backboard 90 x 72 cm
LZ50960	Backboard 90x65cm
LZ12340	Chimney extension 750 mm
LZ12240	Chimney extension 500 mm

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94PBC50B

Features

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 365 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 65 dB dB*

Features

- Push button control for extractor speeds and light
- 3 x power levels
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- 3 x metal grease filter cassettes - dishwasher safe
- For wall mounted installation

Design

- Chimney hood
- Mechanical

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Maximum extraction rate exhaust air 365 m³/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 65 dB(A) re 1 pW
- Extraction rate in recirculation mode:
- Max. normal use: 213 m³/h
- Noise level in recirculation mode:
- Max. normal use: 67 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Power rating: 100 W
- Light Intensity: 94 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 799-975 x 900 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 799-975 x 900 x 500 mm
-
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 53.1 kWh/year*




Optional accessories

- Recirculating kit LZ12240

* In accordance with the EU-Regulation No 65/2014

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94PBC50B

Dimensioned drawings



measurements in mm

