

N 50, Wall-mounted cooker hood, 60 cm, clear glass black printed

D651HM1S0B





В

Optional accessories

Z50XXP0X0 Long Life odor filter (replacement)
 Z51AIA0X0 Standard odor filter (replacement)
 Z51AIR0X0 Long Life recirculation kit (chimless)
 Z51AIS0X0 Long Life recirculation kit
 Z51AIT0X0 Standard recirculation kit (chimless)
 Z51AIU0X0 Standard recirculation kit

Z51AXC1N6 Clean Air Plus recirc. kit external Z51AXK0N0 Chimney extension 1000 mm Z51AXL0N0 Chimney extension 1500 mm

Z53XXB1X6 Clean Air Plus odor filter (replacement)

Z91AXE1S1 Chimney standard black

This sleek black design angled hood incorperates Graphite side trims and black chimney section to match to other cooking products. Advanced features provide customisable lighting solutions and ensure your kitchen is free from cooking odours, allowing you to cook with confidence.

- $\sqrt{\,}$ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- $\sqrt{}$ Intensive speed setting: increases the extraction rate when the steam gets intense
- $\sqrt{\mbox{ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights$
- $\sqrt{\mbox{ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story$

Features

Technical Data

Typology: Chimney

Approval certificates : CE, VDE

Length of electrical supply cord (cm): 130 Height of product, without chimney (mm): 323 Minimum distance above an electric hob: 450 Minimum distance above a gas hob: 600

Net weight (kg): 19.946 Type of control: Electronic

Maximum output air extraction (m3/h): 416 Boost position output recirculating (m3/h): 615.0 Maximum output recirculating air (m3/h): 409 Boost position air extraction (m^3/h): 700

Number of lights (Stck): 2 Noise level (dB(A) re 1 pW): 58 Diameter of air outlet (mm): 120 / 150 Grease filter material: Washable aluminium

EAN code : 4242004210030 Connection rating (W) : 263

Current (A): 10 Voltage (V): 220-240 Frequency (Hz): 60; 50 Plug type: GB plug

Installation type : Wall-mounted





N 50, Wall-mounted cooker hood, 60 cm, clear glass black printed D65IHM1S0B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 416 m³/h Intensive 700 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 58 dB dB*

Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- For wall mounted installation
- Rim ventilation

Design

- Chimney hood
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Easy installation system
- Extraction rate according to EN 61591 max. 416 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust

Max. normal use: 58 dB(A) re 1 pW Intensive: 67 dB(A) re 1 pW

- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Power rating: 263 WLight Intensity: 100 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 590 x 499 mm
- Dimensions recirculating (HxWxD): 988-1258 x 590 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):
 1118 x 590 x 499 mm mounting with outer chimney
 1188-1458 x 590 x 499 mm mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: B*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 56.6 kWh/year*

Optional accessories

- Recirculating kit Z50XXP0X0
- * In accordance with the EU-Regulation No 65/2014



N 50, Wall-mounted cooker hood, 60 cm, clear glass black printed D651HM1S0B



