

N 70, Induction hob, 60 cm, Black T46FD53X2







Optional accessories

Z943SE0 Set of 2 pots and 1 pan

Induction cooktop with TouchControl.

- $\sqrt{}$ Touch Control Control your hob with a simple touch.
- $\checkmark\,$ Combi Induction Merge two circular cooking zones to heat large cookware.
- $\checkmark\,$ Power Move Just slide your cookware to adjust the temperature.
- $\sqrt{\ }$ Power Boost An extra surge of heat when you need fast results.
- $\checkmark\,$ Induction the heat is generated directly in the cookware for precise cooking that stops when power is off.

Features

Technical Data

Product name/family : Cooking zone ceramic Construction type : Built-in Energy input : Electric Total number of positions that can be used at the same time : 4 Required niche size for installation (HxWxD) : $51 \times 560-560 \times$ 490-500 mm Width of the appliance : 592 mm Dimensions : 51 x 592 x 522 mm Dimensions of the packed product (HxWxD) : 126 x 753 x 608 mm Net weight : 11.679 kg Gross weight : 12.8 kg Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic Color of surface : Black Approval certificates : AENOR, CE Length of electrical supply cord : 110 cm EAN code : 4242004232773 Electrical connection rating : 6900 W Voltage : 220-240 V Frequency : 50; 60 Hz



N 70, Induction hob, 60 cm, Black T46FD53X2



Features

Design

- Bevelled front edge
- 60 cm: space for 4 pots or pans.

Flexibility of cooking zones

- Combi zone
- : use bigger cookware by connecting two classic cooking zones into one large zone.
- \bullet Cooking zone front left: 190 mm, 210 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear left: 190 mm, 210 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear right: 145 mm , 1.4 KW (max power 2.2 KW)
- Cooking zone front right: 180 mm, 1.8 KW (max. power 3.1 KW) Usage convenience
- Touch control: control the power with imprinted +/- touch buttons.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function: keep dishes warm at preset low power level.
- Timer with automatic shut off for all zones
- : switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- LED timer for each zone with switch off function and acoustic signal

: an alarm sounds at the end of the time set (e.g. for pasta).

Time saving & efficiency

- Power Boost function for all zones
 boil water faster thanks to 50% more energy than at the highest standard level.
- 2-steps: increase or decrease the power level simply by moving the pot forwards or backwards.
- QuickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).
- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds.

Safety

- 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Control panel suspension: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Main switch: switch off all cooking zones at the touch of a button.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).
- Energy consumption display: shows the electricity consumption of the last cooking process.

Installation

- Dimensions of the product (HxWxD mm): 51 x 592 x 522
- Required niche size for installation (HxWxD mm) : 51 x 560 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 6.9 KW
- Power cord: 1.1 m, Cable included in packaging

N 70, Induction hob, 60 cm, Black T46FD53X2



