

N 50, Wall-mounted cooker hood, 90 cm, clear glass black printed
D95IHM1S0B



COOKING PASSION SINCE 1877



B

The design hood with an inclined front and high power ensures headroom while cooking.

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

Features

Technical Data

Typology : Wall-mounted
Approval certificates : CE, E17D UKCA marking, VDE
Length of electrical supply cord : 130 cm
Height of product, without chimney : 323 mm
Minimum distance above an electric hob : 450 mm
Minimum distance above a gas hob : 650 mm
Net weight : 24.141 kg
Type of control : Electronic
Maximum output air extraction : 416 m³/h
Boost position output recirculating : 469 m³/h
Maximum output recirculating air : 367 m³/h
Boost position air extraction : 700 m³/h
Number of lights (Stck) : 2
Noise level : 58 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242004210221
Connection rating : 263 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 60; 50 Hz
Plug type : GB plug
Installation type : Wall-mounted

Optional accessories

Z51AII1X6	Clean Air Plus recirculation kit
Z51AIROX0	Long Life recirculation kit (chimless)
Z51AISOX0	Long Life recirculation kit
Z51AIV1X6	Clean Air Plus recirc. kit (chimless)
Z51AXK0N0	Chimney extension 1000 mm
Z51AXL0N0	Chimney extension 1500 mm
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z91AXE1S1	Chimney standard black



4 242004 210221

*N 50, Wall-mounted cooker hood, 90 cm, clear
glass black printed
D951HM1S0B*



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 416 m³/h
Intensive 700 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 58 dB dB*

Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- Rim ventilation

Design

- Chimney hood
- Installation: wall
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 58 dB(A) re 1 pW
Intensive: 67 dB(A) re 1 pW
- Power rating: 263 W
- Light Intensity: 90 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 890 x 499 mm
- Dimensions recirculating (HxWxD): 988-1258 x 890 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):
1118 x 890 x 499 mm - mounting with outer chimney
1188-1458 x 890 x 499 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: B*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 56.6 kWh/year*

Optional accessories

- Recirculating kit Z50XXPOX0

* In accordance with the EU-Regulation No 65/2014

N 50, Wall-mounted cooker hood, 90 cm, clear
glass black printed
D95IH M1S0B

Dimensioned drawings

