


iQ300, Wall-mounted cooker hood, 60 cm, clear glass black printed LC67KHM60B



B

Angled extractor hood with outstanding design and high extraction rate for a powerful performance.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ Extremely quiet – The quiet hood that keeps the calm your kitchen.
- ✓ touchControl: quickly and easily manage the power levels and the LED light

Features

Technical Data

Typology : Wall-mounted
 Approval certificates : CE, E17D UKCA marking, VDE
 Length of electrical supply cord : 130 cm
 Height of product, without chimney : 323 mm
 Minimum distance above an electric hob : 450 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 19.983 kg
 Type of control : Electronic
 Maximum output air extraction : 416 m³/h
 Boost position output recirculating : 469 m³/h
 Maximum output recirculating air : 367 m³/h
 Boost position air extraction : 700 m³/h
 Number of lights (Stck) : 2
 Noise level : 58 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 EAN code : 4242003760925
 Connection rating : 263 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation type : Wall-mounted



4 242003 760925

Optional accessories

LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ11AXE61	Chimney standard black
LZ11AXC56	Clean Air Plus recirc. kit external
LZ11AKV16	Clean Air Plus recirc. kit (chimless)
LZ10AXL50	Chimney extension 1500 mm
LZ10AXK50	Chimney extension 1000 mm
LZ10AKS00	Long Life recirculation kit
LZ10AKR00	Long Life recirculation kit (chimless)

iQ300, Wall-mounted cooker hood, 60 cm, clear glass black printed LC67KHM60B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 416 m³/h
- Intensive 700 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 58 dB dB*

Features

- 3 x power levels plus intensive setting
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- Twin channel high performance fan motor
- Automatic intensive revert (6mins)
- 2 x metal grease filter cassettes
- easy to clean Inner frame
- Installation: wall
- Rim ventilation

Design

- Black glass
-
- Chimney hood
- touchControl for extractor speeds and light
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- In recirculation operation chimless use possible
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Installation system: Wall fixing inclined/flat/cube
- Max. extraction rate: 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 58 dB(A) re 1 pW
- Intensive: 67 dB(A) re 1 pW
- Power rating: 263 W
- Light Intensity: 100 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 590 x 499 mm
- Dimensions recirculating, chimney (HxWxD): 988-1258 x 590 x 499 mm
-
- Dimensions recirculating, chimless (HxWxD): 452 mm x 590 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 1118 x 590 x 499 mm - mounting with outer chimney
- 1188-1458 x 590 x 499 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: B*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 56.6 kWh/year*

Optional accessories

- Recirculating kit LZ11AXC56

* In accordance with the EU-Regulation No 65/2014

iQ300, Wall-mounted cooker hood, 60 cm, clear glass black printed LC67KHM60B

Dimensioned drawings

