


iQ300, Island cooker hood, 90 cm, clear glass LF97GBM50B



The island hood features an efficient extraction rate in the distinctive Siemens design.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ Extremely quiet – The quiet hood that keeps the calm your kitchen.
- ✓ touchControl: quickly and easily manage the power levels and the LED light

Features

Technical Data

Typology : Island/Ceilling
Approval certificates : CE, E17D UKCA marking, VDE
Length of electrical supply cord : 130 cm
Height of the chimney : 698-878/698-998 mm
Height of product, without chimney : 46 mm
Minimum distance above an electric hob : 550 mm
Minimum distance above a gas hob : 650 mm
Net weight : 30.075 kg
Type of control : Electronic
Maximum output air extraction : 429 m³/h
Boost position output recirculating : 527 m³/h
Maximum output recirculating air : 390 m³/h
Boost position air extraction : 732 m³/h
Number of lights (Stck) : 4
Noise level : 60 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242003832110
Connection rating : 256 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Plug type : GB plug
Installation type : Island

Optional accessories

LZ53650	Standard recirculation kit
LZ53251	Standard odor filter (replacement)
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ21CXC56	Clean Air Plus recirc. kit external
LZ12500	Extension for mounting kit 500 mm
LZ12400	Adapter for roof inclination front/back
LZ12375	Chimney extension 1600 mm
LZ12300	Adapter for roof inclination left/right



4 242003 832110

iQ300, Island cooker hood, 90 cm, clear glass LF97GBM50B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 429 m³/h
- Intensive 732 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 60 dB dB*

Features

- touchControl with Electronic display
- 4 x 1.5W LED
- 3 x power levels plus intensive setting
- Automatic intensive revert (6mins)
- Steel filter cover
- 2 x metal grease filter cassettes

Design

- Stainless Steel
- Stainless steel hood with glass canopy
- Installation: Ceiling
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 732 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 60 dB(A) re 1 pW
- Intensive: 71 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode:
- Max. normal use: 390 m³/h
- Intensive: 527 m³/h
- Noise level in recirculation mode:
- Max. normal use: 67 dB(A) re 1 pW
- Intensive: 73 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 502 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating, chimney (HxWxD): 744-1044 x 898 x 600 mm
-
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 71.3 kWh/year*

Optional accessories

- Recirculating kit LZ31CXB14

* In accordance with the EU-Regulation No 65/2014

iQ300, Island cooker hood, 90 cm,
clear glass
LF97GBM50B

Dimensioned drawings

