



N 90, Induction hob, 90 cm, Black  
T50FS41X0



COOKING PASSION SINCE 1877



#### FlexInduction Hob with TwistPad control.

- ✓ TwistPadFire® – our removable, magnetic, illuminated control dial that gives you precise control over all cooking zones.
- ✓ Flex Induction – Your hob detects and heats your individual cookware.
- ✓ Panoramic Induction Hob – space for three pots or pans side by side for comfortable cooking.
- ✓ Power Move – Just slide your cookware to adjust the temperature.
- ✓ Frying Sensor – Monitors the temperature to prevent scorching.

#### Features

##### Technical Data

Product name/family : Cooking zone ceramic  
Construction type : Built-in  
Energy input : Electric  
Total number of positions that can be used at the same time : 4  
Required niche size for installation (HxWxD) : 51 x 880-880 x 330-330 mm  
Width of the appliance : 903 mm  
Dimensions : 51 x 903 x 346 mm  
Dimensions of the packed product (HxWxD) : 126 x 1031 x 472 mm  
Net weight : 14.835 kg  
Gross weight : 16.0 kg  
Residual heat indicator : Separate  
Location of control panel : Hob front  
Basic surface material : Ceramic  
Color of surface : Black  
Approval certificates : AENOR, CE  
Length of electrical supply cord : 110 cm  
EAN code : 4242004195658  
Electrical connection rating : 7400 W  
Voltage : 220-240 V  
Frequency : 50; 60 Hz

#### Optional accessories

|         |  |
|---------|--|
| Z9410X1 | Stainless Steel roaster with glas lid    |
| Z9415X1 | Steaming Rack for Stainless Steel roaste |
| Z9416X2 | Griddle Plate                            |
| Z9417X2 | Teppan Yaki (large)                      |
| Z943SE0 | Set of 2 pots and 1 pan                  |



4 242004 195658

*N 90, Induction hob, 90 cm, Black*  
T50FS41X0



COOKING PASSION SINCE 1877

## Features

### Design

- Bevelled front edge
- 90 cm: space for 4 pots or pans.

### Flexibility of cooking zones

- 2 Flex zones: use cookware of any shape or size anywhere within the 40cm long zone.
- Cooking zone front left: 210 mm, 200 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear left: 210 mm, 200 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear right: 210 mm, 200 mm, 2.2 KW (max power 3.7 KW)
- Cooking zone front right: 210 mm, 200 mm, 2.2 KW (max. power 3.7 KW)

### Usage convenience

- TwistPad® Fire: directly control the power with the illuminated and removable magnetic dial.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function: keep dishes warm at preset low power level.
- Timer with automatic shut off for all zones  
: switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- LED timer for each zone with switch off function and acoustic signal  
: an alarm sounds at the end of the time set (e.g. for pasta).
- Count up timer  
: shows how much time has passed since starting the timer (e.g. for potatoes).

### Time saving & efficiency

- Power Boost function for all zones  
: boil water faster thanks to 50% more energy than at the highest standard level.
- PanBoost: heat up pans faster than at the highest standard level while protecting the pan coating.
- PowerMove with 3 levels: increase or decrease the power level simply by moving the pot forwards or backwards.
- QuickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).
- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds.

### Cooking assistance

- 5 frying levels: prevents overcooking with the automatic temperature regulation of the integrated sensor.

### Safety

- 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Control panel suspension: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Main switch: switch off all cooking zones at the touch of a button.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).
- Energy consumption display: shows the electricity consumption of the last cooking process.

### Installation

- Dimensions of the product (HxWxD mm): 51 x 903 x 346
- Required niche size for installation (HxWxD mm) : 51 x 880 x (330 - 330)
- Min. worktop thickness: 16 mm
- Connected load: 7.4 KW
- 4.6kW power output (20A); current management options for 16A, 13A or 10A connection: limit the maximum power if needed (depends on fuse protection of electric installation).
- Power cord: 1.1 m, Cable included in packaging

N 90, Induction hob, 90 cm, Black  
T50FS41X0



COOKING PASSION SINCE 1877

Dimensioned drawings

