





Optional accessories

Z9410X1 Stainless Steel roaster with glas lidZ9415X1 Steaming Rack for Stainless Steel roaste

Z9416X2 Griddle Plate
Z9417X2 Teppan Yaki (large)
Z943SE0 Set of 2 pots and 1 pan
Z9914X0 Connecting strip

FlexInduction Hob with TFT touch-display.

- $\sqrt{\,}$ TFT Display Vivid images help you find your functions with ease.
- $\sqrt{\mbox{ Flex Induction}}$ Your hob detects and heats your individual cookware.
- $\sqrt{\ }$ Cooking Assistant Knows the right temperature for your dish.
- $\sqrt{}$ Power Move Just slide your cookware to adjust the temperature.
- $\sqrt{\ }$ Power Transfer when you reposition a pot, your settings automatically follow the cookware.

Feature

Technical Data

Product name/family : Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 5 Required niche size for installation (HxWxD) : $51 \times 880-880 \times 10^{-2}$

490-500 mm

Width of the appliance : 918 mm Dimensions : 51 x 918 x 546 mm

Dimensions of the packed product (HxWxD) : 126 x 1073 x 608 mm

Net weight : 20.753 kg Gross weight : 22.5 kg

Residual heat indicator: Separate Location of control panel: Hob front Color of surface: Black, Stainless steel Color of frame: Stainless steel Approval certificates: AENOR, CE Length of electrical supply cord: 110 cm

EAN code: 4242004211464

Electrical connection rating: 11100 W

Voltage: 220-240 V Frequency: 60; 50 Hz





Features

Design

- Ceramic glass on stainless steel trim
- 90 cm: space for 5 pots or pans.

Flexibility of cooking zones

- 3 Flex Induction zones: use cookware of any shape or size anywhere within the 40cm long zone.
- Cooking zone front left: 240 mm, 200 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear left: 240 mm, 200 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone middle: 300 mm, 240 mm, 2.6 KW (max. power 3.7 KW)
- Cooking zone rear right: 240 mm, 200 mm, 2.2 KW (max power 3.7 KW)
- Cooking zone front right: 240 mm, 200 mm, 2.2 KW (max. power 3.7 KW)

Usage convenience

- FullTouch TFT Display: easily operate the hob using the touch display and explore all available functions thanks to full-text information and images.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function: keep dishes warm at preset low power level.
- Timer with automatic shut off for all zones
 : switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- LED timer for each zone with switch off function and acoustic signal
- : an alarm sounds at the end of the time set (e.g. for pasta).
- Count up timer
- : shows how much time has passed since starting the timer (e.g. for potatoes).

Time saving & efficiency

- Power Boost function for all zones
 : boil water faster thanks to 50% more energy than at the highest standard level.
- PanBoost: heat up pans faster than at the highest standard level while protecting the pan coating.
- PowerMove with 3 levels: increase or decrease the power level simply by moving the pot forwards or backwards.
- PowerTransfer: when moving a pot to a different cooking zone, this feature transfers all previous settings to the new zone at the touch of a button.
- QuickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).
- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds.

Cooking assistance

- Dish categories Use TFT Control to assist in cooking dishes to perfection: easily find the right temperature setting for a certain dish in the touch display.
- 5 frying levels: prevents overcooking with the automatic temperature regulation of the integrated sensor.

Connectivity

- Home Connect with Remote Monitoring: check if the hob is switched off even when not at home, and find recipes or additional functions in the Home Connect app.
- Hob Hood Control hood control (with Wi-Fi enabled hood): automatically activates the hood when cooking, thanks to the WiFi connection of hob and suitable hood.

Safety

- 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Control panel suspension: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Main switch: switch off all cooking zones at the touch of a button.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).
- Energy consumption display: shows the electricity consumption of the last cooking process.



Features

Installation

- Dimensions of the product (HxWxD mm): 51 x 918 x 546
- Required niche size for installation (HxWxD mm) : 51 x 880 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 11.1 KW
- Power cord: 1.1 m, Cable included in packaging



