

iQ500, Canopy cooker hood, 52 cm, Stainless steel LB57574GB



The powerful canopy cooker hood is concealed in a unit above the hob.

✓ LED lights: for optimal visibility and ambience while cooking.

Features

Technical Data

Typology : Built-in/Built-under
Approval certificates : CE, VDE
Length of electrical supply cord : 150 cm
Required niche size for installation (HxWxD) : 418mm x 496.0mm x 264mm mm
Minimum distance above an electric hob : 500 mm
Minimum distance above a gas hob : 650 mm
Net weight : 7.310 kg
Type of control : Electronic
Maximum output air extraction : 560 m³/h
Boost position output recirculating : 581 m³/h
Maximum output recirculating air : 533 m³/h
Boost position air extraction : 615 m³/h
Number of lights (Stck) : 2
Noise level : 67 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242003686249
Connection rating : 252 W
Fuse protection : 3 A
Voltage : 220-240 V
Frequency : 50 Hz
Plug type : GB plug
Installation type : Built-in



Optional accessories

LZ55750	Standard recirculation kit
LZ55651	Standard odor filter (replacement)
LZ11IXC16	Clean Air Plus recirc. kit external
LZ11IXB16	Clean Air Plus odor filter (replacement)
LZ11ITD11	Long Life recirculation kit external

iQ500, Canopy cooker hood, 52 cm, Stainless steel LB57574GB

Features

Key Information

- Soft touch button control for extractor speeds and light
- 3 x power levels plus intensive setting
- Automatic intensive revert
- 2 x 1W LED lights
- 1 x metal grease filter cassette
- Steel filter cover, Steel filter cover
- Rim ventilation

Design

- 52 cm wide
- Stainless Steel
- Installation: Cabinet
- Electronic control via Soft touch button control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
- Max. Normal use 560 m³/h
- Intensive 615 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 67 dB(A) re 1 pW
- Intensive: 70 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode:
- Max. normal use: 533 m³/h
- Intensive: 581 m³/h
- Noise level in recirculation mode:
- Max. normal use: 72 dB(A) re 1 pW
- Intensive: 74 dB(A) re 1 pW
- Power rating: 252 W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Dimensions (WxD): 520 x 300 mm
- Built-in dimensions (HxWxD): 418 x 496 x 264 mm
- Dimensions exhaust air (HxWxD): 418-418 x 520 x 300 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Average Energy Consumption: 90.2 kWh/year*
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*

* In accordance with the EU-Regulation No 65/2014

iQ500, Canopy cooker hood, 52 cm,
Stainless steel
LB57574GB

Dimensioned drawings

