

**Serie | 2, Integrated cooker hood, 60 cm, silver  
DEM66AC00B**

**B**



**Optional accessories**

DWZ0IM0A0 : Standard odor filter (replacement)

**Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.**

- **LED Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- An impressive extraction rate of m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- 3-speed power Level options to suit your cooking style and recipes.
- Ducted or Non-ducted Options

**Technical Data**

Typology : Built-in/Built-under  
Approval certificates : CE  
Length of electrical supply cord : 150 cm  
Minimum distance above an electric hob : 500 mm  
Minimum distance above a gas hob : 650 mm  
Net weight : 11.940 kg  
Type of control : mechanical  
Number of speed settings : 3  
Maximum output air extraction : 625 m<sup>3</sup>/h  
Maximum output recirculating air : 416 m<sup>3</sup>/h  
Number of lights (Stck) : 2  
Noise level : 70 dB(A) re 1 pW  
Diameter of air outlet : 150 / 120 mm  
Grease filter material : Washable aluminium  
EAN code : 4242005041121  
Connection rating : 256 W  
Fuse protection : 10 A  
Voltage : 220-240 V  
Frequency : 50; 60 Hz  
Plug type : GB plug  
Installation type : Wall-mounted



4 242005 041121

**Serie | 2, Integrated cooker hood, 60 cm,  
silver  
DEM66AC00B**

**Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.**

---

**Key performance features:**

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 625 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB\*

**Features**

- Push button control for extractor speeds and light
- 3 power levels
- 2 x 3W LED
- Single motor
- 2 removable metal grease filter cassettes

**Design**

- Integrated hood
- Installation: Between Cupboards
- Push button control
- Mechanical

**Performance/technical information**

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 68.4 kWh/year\*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm

**Optional accessories**

- Recirculating kit DWZ0IM0A0

*\* In accordance with the EU-Regulation No 65/2014*

**Serie | 2, Integrated cooker hood, 60 cm,  
silver  
DEM66AC00B**

