# N 30, Built-in oven, 60 x 60 cm, Stainless steel B3CCCOANOB



COOKING PASSION SINCE 1877



Α





#### Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11TF36X0 3 level telescopic rails, full ext

Z11TI15X0 Cliprails

Z12CQ10A0 Grill tray, anthracite enamelled

Z1913X0 Baking Stone

Built-in Slide&Hide® oven with fixed handle - unrestricted access to the oven interior thanks to the fully retracting oven door

 $\sqrt{\mbox{ Hide}^{\mbox{\tiny B}}}$  – The fully retracting oven door.

 $\sqrt{\mbox{CircoTherm}^{\mbox{\tiny 0}}}$  – Smart hot-air solution that lets you bake on up to three levels at once.

 $\sqrt{\mbox{ LED-Display}}$  - simple, straightforward for clear reading

#### Features

#### Technical Data

Color / Material Front : Stainless steel Construction type : Built-in Integrated Cleaning system : No

Required niche size for installation (HxWxD) : 585-595 x 560-568 x

550 mm

Dimensions : 595 x 594 x 548 mm

Dimensions of the packed product (HxWxD) :  $660 \times 690 \times 660$  mm

Control Panel Material : Stainless steel

Door Material : Glass Net weight : 35.174 kg Usable volume of cavity : 71 l

Cooking method: Conventional heat, Full width grill, Hot Air, Hotair

gentle, Hot air grilling First cavity material : Other Oven control : mechanical Number of interior lights : 1 Approval certificates : CE, VDE

Length of electrical supply cord: 120 cm

EAN code: 4242004248705 Number of cavities (2010/30/EC): 1 Energy efficiency rating: A

Energy consumption per cycle conventional (2010/30/EC): 1.04

kWh/cycle

Energy consumption per cycle forced air convection (2010/30/EC) :

0.81 kWh/cycle

Energy efficiency index (2010/30/EC): 95.3 %

Connection rating: 2990 W Fuse protection: 13 A Voltage: 220-240 V Frequency: 50; 60 Hz Plug type: no plug





#### Features

#### Design

- LED Display (Red)
- Elongated designed dials, Retractable control dials, Bevelled oval controls
- Slide&Hide® with fixed handle
- Cavity inner surface: enamel grey
- Bar handle
- 4 shelf positions

#### Features

- Heating up indicator Automatic start
- Control panel lock
- Interior halogen light

#### Cleaning

• Full glass inner door

#### Programmes/functions

- Oven with 5 main functions heating methods: CircoTherm®, Top/bottom heat, Circo-roasting, Full surface grill, CircoTherm® gentle
- Cooling fan
- Temperature range 50 °C 275 °C

### Accessories

• 2 x combination grid, 1 x universal pan

# Performance/technical information

- Cavity volume: 71 litre
- Energy efficiency rating (acc. EU Nr. 65/2014): A

Energy consumption per cycle in conventional mode: 1.04 kWh Energy consumption per cycle in fan-forced convection mode: 0.81 kWh


Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre

- Total connected load electric: 2.99 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm
- Please refer to the dimensions provided in the installation manual





# COOKING PASSION SINCE 1877


# Dimensioned drawings



A: 19.5 mm B: Space for appliance connection 320 x 115 mm







If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm