

N 50, Wall-mounted cooker hood, 90 cm, clear glass black printed  
D95IH M1S0B



COOKING PASSION SINCE 1877



B



The sleek black glass design angled hood ensures your kitchen is free from cooking smells thanks to advanced features which let you get on with your cooking

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

#### Features

##### Technical Data

Typology : Chimney  
Approval certificates : CE, VDE  
Length of electrical supply cord (cm) : 130  
Height of product, without chimney (mm) : 323  
Minimum distance above an electric hob : 450  
Minimum distance above a gas hob : 600  
Net weight (kg) : 24.512  
Type of control : Electronic  
Maximum output air extraction (m<sup>3</sup>/h) : 416  
Boost position output recirculating (m<sup>3</sup>/h) : 557.0  
Boost position air extraction (m<sup>3</sup>/h) : 700  
Number of lights (Stck) : 2  
Noise level (dB(A) re 1 pW) : 58  
Diameter of air outlet (mm) : 120 / 150  
Grease filter material : Washable aluminium  
EAN code : 4242004210221  
Connection rating (W) : 263  
Current (A) : 10  
Voltage (V) : 220-240  
Frequency (Hz) : 60; 50  
Plug type : GB plug  
Installation type : Wall-mounted



4 242004 210221

#### Optional accessories

Z50XXP0X0 Long Life odor filter (replacement)  
Z51AIA0X0 Standard odor filter (replacement)  
Z51AIROX0 Long Life recirculation kit (chimless)  
Z51AIS0X0 Long Life recirculation kit  
Z51AIT0X0 Standard recirculation kit (chimless)  
Z51AIU0X0 Standard recirculation kit  
Z51AXK0N0 Chimney extension 1000 mm  
Z51AXL0N0 Chimney extension 1500 mm  
Z53XXB1X6 Clean Air Plus odor filter (replacement)  
Z91AXE1S1 Chimney standard black

*N 50, Wall-mounted cooker hood, 90 cm, clear  
glass black printed  
D95JHM1S0B*

## Features

### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 Ø 15 cm: max. Normal use 416 m³/h Intensive 700 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 58 dB dB\*

### Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- For wall mounted installation
- Rim ventilation

### Design

- Chimney hood
- Electronic controls

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Easy installation system
- Extraction rate according to EN 61591 max. 416 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 58 dB(A) re 1 pW Intensive: 67 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Extraction rate in recirculation mode: Max. normal use: 388 m³/h Intensive: 557 m³/h
- Noise levels in recirculation mode: Max. normal use: 66 dB(A) re 1 pW Intensive: 75 dB(A) re 1 pW
- Power rating: 263 W
- Light Intensity: 90 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 890 x 499 mm
- Dimensions recirculating (HxWxD): 988-1258 x 890 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD): 1118 x 890 x 499 mm - mounting with outer chimney 1188-1458 x 890 x 499 mm - mounting with telescopic chimney
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: B\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 56.6 kWh/year\*

### Optional accessories

- Recirculating kit Z50XXPOX0

\* In accordance with the EU-Regulation No 65/2014