Data sheet for household cooker hoods
In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele						
Model name / identifier		DA 396-7				
Annual Energy Consumption (AEC)						
(AEC _{Haube})	kWh/year	59,1				
Energy efficiency class						
Based on standard test results for 24 hours. Actual ene	ergy					
consumption will depend on how the appliance is used	and where					
it is located.		С				
Energy efficiency index (EEI)						
(EEI _{Haube})		75,8				
Fluid Dynamic Efficiency (FDE) (FDE _{Haube})		17,0				
Fluid Dynamic Efficiency class						
A (most efficient) to G (least efficient)		D				
Lighting Efficiency (LE) (LE _{Haube})	lx/W	60,0				
Lighting Efficiency class						
A (most efficient) to G (least efficient)	0/	Α				
Grease Filtering Efficiency Grease Filtering Efficiency class	%	95,1				
A (most efficient) to G (least efficient)		Α				
, , ,	m³/h					
Airflow at best efficiency point		316,5				
Air flow (min. speed)	m³/h	150				
Air flow (max. speed)	m³/h	350				
Air flow (intensive or boost setting)	m³/h	500				
Max. air flow (Q) (Q _{max})	m³/h	500				
Air pressure at best efficiency point	Pa	209				
Airborne acoustical A-weighted sound power emissions						
(min. speed)	dB	41				
Airborne acoustical A-weighted sound power emissions						
(max. speed)	dB	55				
Airborne acoustical A-weighted sound power emissions		60				
(intensive or boost setting)	dB W	62 108,0				
Electrical power input at best efficiency point Power consumption in off mode (P _o)	W	108,0				
		0.00				
Power consumption in standby mode (P _s) Nominal power of lighting system	W	0,20 6,0				
Average illumination of the lighting system on the cooki		0,0				
surface	irig İx	360				
Time increase factor	1.	1,4				
Time morease ractor		1,7	_	 		