

N 50, Wall-mounted cooker hood, 90 cm, Stainless steel  
D94QFM1N0B



COOKING PASSION SINCE 1877



A

Our classic design hood with a modern twist - experience the slim pyramid hood.

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story
- ✓ High Extraction Rate – ensures a clear view while cooking thanks to an efficient motor technology

#### Features

##### Technical Data

Typology : Wall-mounted  
Approval certificates : CE, E17D UKCA marking, VDE  
Length of electrical supply cord : 130 cm  
Height of the chimney : 582-912/582-1022 mm  
Height of product, without chimney : 94 mm  
Minimum distance above an electric hob : 550 mm  
Minimum distance above a gas hob : 650 mm  
Net weight : 11.963 kg  
Type of control : Electronic  
Maximum output air extraction : 389 m<sup>3</sup>/h  
Boost position output recirculating : 441 m<sup>3</sup>/h  
Maximum output recirculating air : 337 m<sup>3</sup>/h  
Boost position air extraction : 642 m<sup>3</sup>/h  
Number of lights (Stck) : 2  
Noise level : 61 dB(A) re 1 pW  
Diameter of air outlet : 120 / 150 mm  
Grease filter material : Washable aluminium  
EAN code : 4242004224211  
Connection rating : 220 W  
Fuse protection : 10 A  
Voltage : 220-240 V  
Frequency : 50; 60 Hz  
Plug type : GB plug  
Installation type : Wall-mounted

#### Optional accessories

Z51DXA0X0	Standard odor filter (replacement)
Z51DXI1X6	Clean Air Plus recirculation kit
Z51DXU0X0	Standard recirculation kit
Z51FXC1N6	Clean Air Plus recirc. kit external
Z51FXJ0X0	Long Life recirculation kit
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5895N0	Stainless steel back panel 900 mm
Z5905N0	Chimney extension 1000 mm
Z5915N0	Chimney extension 1500 mm



4 242004 224211

*N 50, Wall-mounted cooker hood, 90 cm, Stainless steel*  
*D94QFM1N0B*



COOKING PASSION SINCE 1877

## Features

### Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 389 m<sup>3</sup>/h  
Intensive 642 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 61 dB dB\*

### Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- Installation: wall

### Design

- Chimney hood
- Electronic controls

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 642 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 61 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 61 dB(A) re 1 pW  
Intensive: 70 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 61 dB (A) re 1pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:  
Extraction rate in recirculation mode:  
Max. normal use: 337 m<sup>3</sup>/h  
Intensive: 441 m<sup>3</sup>/h  
Noise level in recirculation mode:  
Max. normal use: 70 dB(A) re 1 pW  
Intensive: 74 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 214 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 676-1006 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 676-1116 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
744 x 900 x 500 mm - mounting with outer chimney  
874-1204 x 900 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 42.4 kWh/year\*

### Optional accessories

- Recirculating kit Z50XXPOX0

\* In accordance with the EU-Regulation No 65/2014

N 50, Wall-mounted cooker hood, 90 cm, Stainless steel  
D94QFM1N0B

Dimensioned drawings

