

iQ500, Gas hob, 75 cm, Stainless steel EC7A5RB90





The gas hob with stepFlame Technology for precise flame control in nine steps.

- ✓ stepFlame Technology Precise flame control with nine different settings.
- ✓ Dual Wok Burner 5 kW Go from simmer to stir-fry on one burner.
- ✓ High-quality materials and workmanship continuous cast-iron pan supports.
- ✓ Biomethane ready Power your gas hob with renewable biomethane gas.
- ✓ The extremely convenient sword knob makes it easy to control and monitor the power level selected.

Feature

Technical Data

Product name/family: gas hob w integrated controls

Construction type : Built-in

Energy input: Gas

Total number of positions that can be used at the same time: 5

Type of control setting devices : sword knobs

Required niche size for installation (HxWxD) : 45 x 560-562 x 480-492

mm

Width of the appliance : 750 mm Dimensions : 45 x 750 x 520 mm

Dimensions of the packed product (HxWxD): 145 x 793 x 597 mm

Net weight : 15.039 kg Gross weight : 16.5 kg

Residual heat indicator: without Location of control panel: Hob front Basic surface material: Stainless steel Color of surface: Stainless steel Color of frame: Stainless steel

Approval certificates : CE, Eurasian, Ukraine Length of electrical supply cord : 100 cm

EAN code : 4242003676134 Electrical connection rating : 1 W Gas connection rating : 12500 W

Fuse protection : 3 A Voltage : 220-240 V Frequency : 50; 60 Hz





iQ500, Gas hob, 75 cm, Stainless steel EC7A5RB90

Features

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- Step Flame technology 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner gas hob including:
- Including 1 dual control wok burner: use an extra wide power range, separately controlling two flame rings.
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: wok burner up to 5 KW (depending on gas type)
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety


• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU)
- Natural gas L 25 mbar (NL)
- Liquid gas G30,31 28-30/37mbar
- Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- •
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 750 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 12.5 KW



iQ500, Gas hob, 75 cm, Stainless steel EC7A5RB90



*min. 150

* Minimum distance from the hob cut-out to the wall Position of gas connection in the cut-out

480-490+2

min. 600

*** With fitted oven underneath, possibly more; see space requirements for the oven measurements in mm