

## iQ100, Gas hob, 60 cm, Stainless steel EB6B5PB60



A gas cooktop with side-mounted controls.

- ✓ High-quality materials and workmanship – continuous cast-iron finish pan supports.
- ✓ Biomethane ready – Power your gas hob with renewable biomethane gas.
- ✓ The sword knob combines highest ease of use with modern design.
- ✓ The uniquely beautiful stainless-steel surface design.

### Features

#### Technical Data

Product name/family : gas hob w integrated controls  
 Construction type : Built-in  
 Energy input : Gas  
 Total number of positions that can be used at the same time : 4  
 Type of control setting devices : sword knobs  
 Required niche size for installation (HxWxD) : 45 x 560-562 x 480-492 mm  
 Width of the appliance : 580 mm  
 Dimensions : 45 x 580 x 510 mm  
 Dimensions of the packed product (HxWxD) : 141 x 651 x 578 mm  
 Net weight : 7.095 kg  
 Gross weight : 8.0 kg  
 Residual heat indicator : without  
 Location of control panel : Hob lateral  
 Basic surface material : Stainless steel  
 Color of surface : Stainless steel  
 Color of frame : Stainless steel  
 Approval certificates : CE  
 Length of electrical supply cord : 100 cm  
 EAN code : 4242003687062  
 Electrical connection rating : 1 W  
 Gas connection rating : 7400 W  
 Fuse protection : 3 A  
 Voltage : 220-240 V  
 Frequency : 60; 50 Hz



4 242003 687062

## iQ100, Gas hob, 60 cm, Stainless steel EB6B5PB60

### Features

#### Design

- Stainless steel surface
- cast iron finish pan supports with rubber feet

#### Usage convenience

- Design co-ordinated control dials: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

#### Burners and power

- 4 burner gas hob including:
- Left front: High-speed burner up to 3 KW (depending on gas type)
- Left rear: Standard burner up to 1.7 KW (depending on gas type)
- Right rear: Standard burner up to 1.7 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

#### Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

#### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU)
- Natural gas L 25 mbar (NL)
- Liquid gas G30,31 28-30/37mbar
- Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- 
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 56 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.4 KW

## Dimensioned drawings

