N 30, Built-under double oven, Stainless steel I1GCC0AN0B





Included accessories

1 x combination grid, 1 x universal pan

Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11TI15X0 Cliprails

Z12CQ10A0 Grill tray, anthracite enamelled

Z1913X0 Baking Stone

Built under double oven - twice as flexible, twice as fast - bake or roast multiple dishes at the same time.

 $\sqrt{\ }$ LED-Display - simple, straightforward for clear reading

Features

Technical Data

Color / Material Front : Stainless steel

Construction type : Built-in Integrated Cleaning system : No Dimensions : $717 \times 594 \times 550 \,$ mm

Dimensions of the packed product (HxWxD) : $790 \times 690 \times 660$ mm

Control Panel Material: Stainless steel

Door Material : Glass Net weight : 41.441 kg Usable volume of cavity : 47 l

Cooking method : Conventional heat, Full width grill, Hot Air, Hotair

gentle, Hot air grilling Oven control : mechanical Number of interior lights : 1 Approval certificates : CE, VDE EAN code : 4242004234142 Energy efficiency rating : A

Energy consumption per cycle conventional (2010/30/EC): 0.84

kWh/cycle

Energy consumption per cycle forced air convection (2010/30/EC) :

0.71 kWh/cycle

Energy efficiency class (2010/30/EC) - cavity 2 : B

Energy consumption per cycle conventional - cavity 2 (2010/30/EC) :

0.83 kWh/cycle

Energy efficiency index (2010/30/EC): 94.7 %

Energy efficiency index cavity 2 (2010/30/EC): 120.3 %

Connection rating: 5300 W Fuse protection: 25 A Voltage: 220-240 V Frequency: 50 Hz

Plug type : fixed connection, no plug





Feature:

- LED Display (Red)
- Interior halogen light

Features

- Control panel lock
- Cavity (inner surface) bottom: enamel grey
- Full glass inner door

Top oven additional features

- Cavity volume: 34 Litre
- Cavity (inner surface) top: Enamel grey
- Door hinge small cavity: bottom

Main oven additional features


- Cavity volume: 47 litre
- Door hinge big cavity: Drop down door
- Oven with 3 heating methods: Top/bottom heat, Full surface grill, Small area grill
- Temperature range 50 °C 275 °C
- Oven with 5 heating methods: CircoTherm®, Top/bottom heat, Circo-roasting, Full surface grill, CircoTherm® gentle
- 1 x combination grid, 1 x universal pan


Performance/technical information

- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 717 mm x 594 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



Dimensioned drawings





measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	39	40
Full-surface induction hob	49	50
Gas hob	29	40
Electric hob	29	32

