


iQ100 EH601FEB1E Induction Hob Flush fitting design/installation 572 mm

















Induction cooktop with innovative features that enable highly flexible cooking in any situation.

- ✓ Innovative induction technology is one of the quickest, safest and most efficient methods of cooking.
- \checkmark Shorter heating times with up to 50% more power thanks to the powerBoost function.
- ✓ The touchSlider allows the hob temperature to be controlled by entering it directly or by moving the slider with a single finger.

Feature

Technical Data

Product name/family : Cooking zone ceramic

Construction type : Built-in Source of energy : Electric

Total number of positions that can be used at the same time: 4 Required niche size for installation (HxWxD): 56 x 560-576 x 500-516

Width (mm): 572

Dimensions of the product (mm) : $56 \times 572 \times 512$

Net weight (kg): 12.0 Gross weight (kg): 13.0

Residual heat indicator : Separate

Control panel: Front

Basic surface material : Ceramic

Color of surface : Black

Approval certificates : AENOR, CE Length of electrical supply cord (cm) : 110

EAN code: 4242003716045

Electrical connection rating (W): 7400

Current (A) : 32; 2*16 Nominal power (kW) : 220-240

Frequency (Hz) : 60; 50





iQ100 EH601FEB1E Induction Hob Flush fitting design/installation 572 mm

Features

Control:

• touchSlider control

Special features

- •
- Ring zone
- 4 induction cooking zones
- reStart function
- Timer for all zones Acoustic signal
- 17 power levels
- Power boost setting
- Energy Consumption Display

Safety Features

- Automatic pan recognition
 Connection current management (20, 16, 13, 10 Amps options)
 Automatic safety switch off
 Control panel lock
- 2 stage residual heat indicators
- Main on/off switch

Power and size:

Cooking zones: 1 x Ø 180 mm, 1.8 KW (max. Power levels 3.1 KW) Induction; 1 x Ø 180 mm, 1.8 KW (max. Power levels 3.1 KW) Induction; 1 x Ø 145 mm, 1.4 KW (max. Power levels 2.2 KW) Induction; 1 x Ø 210 mm, 2.2 KW (max. Power levels 3.7 KW) Induction

Technical information

- Installation measurements: 560 mmx500 mm
- Connection cable (1.1 M)
- Min. worktop thickness: 30 mm
- Connected load: 7.4 kW
- Cable included in packaging



iQ100 EH601FEB1E Induction Hob Flush fitting design/installation 572 mm

