

iQ500 EP9A6SB90 90 cm, hob, Hard Glass







Gas cooktop with stepFlame Technology for precise flame control in nine steps.

- ✓ stepFlame Technology: precise heat control with nine different flame steps.
- ✓ This wok burner with 4.0 kW of power is ideal for a wide variety of foods, even in large quantities.
- ✓ Siemens top sheet design for a flush or slightly raised built-in solution.
- ✓ Extremely heat-resistant and easy to clean the modern glass ceramic surface.
- ✓ High-quality materials and workmanship continuous cast-iron pan supports.

Feature

Technical Data

Product name/family: gas hob w integrated controls

Construction type : Built-in Source of energy : Gas

Total number of positions that can be used at the same time : 5 Required niche size for installation (HxWxD) : 45 x 850-852 x 490-502

Width (mm): 915

Dimensions of the product (mm): 45 x 915 x 520

Net weight (kg): 20.0 Gross weight (kg): 22.0 Residual heat indicator: without

Control panel: Front

Basic surface material : Hard Glass

Color of surface : Black Color of frame : Black Approval certificates : CE

Length of electrical supply cord (cm): 150

EAN code: 4242003742617 Electrical connection rating (W): 2 Gas connection rating (W): 11500

Current (A): 3

Nominal power (kW) : 220-240 Frequency (Hz) : 60; 50





iQ500 EP9A6SB90 90 cm, hob, Hard Glass

Features

Design

- Easy to clean Tempered Glass surface.
- Cast iron pan supports with rubber feet
- High efficiency burner set

Special features

- Step Flame technology 9 steps
- Design co-ordinated control dials
- Ignition via control dials

Power and size:

- 5 burner gas hob including:
- 4 gas + wok (Left)
- Right rear: High-speed burner 3 KW
- Left: Wok burner 4 KW
- Center rear: 1.75 KW
- Center front: Economy burner 1 KW
- Right front: Standard burner 1.75 KW

Safety Features

- Factory set for connection to mains gas
- Flame failure safety device

Accessories

• LPG jets (28-30/37mbar) included

Technical information

• 150 cm Cable



iQ500 EP9A6SB90 90 cm, hob, Hard Glass

Dimensioned drawings For installing flush with surrounding min. 50 surfaces 921 850 Chamfer 110±8.5 max. 1 mm measurements in mm min. 50 *min. 150 490-500+2 min. 600 ***min. 30 * Minimum distance from the hob cut-out to the wall ** Position of gas connection in the cut-out *** With fitted oven underneath, possibly more; see space requirements for the oven measurements in mm