


iQ300
LC87KHM60B
Angled design
Chimney hood
Black
80 cm

A



Angled extractor hood with outstanding design and high extraction rate for a powerful performance.

- ✓ The powerful motor with an high extraction rate of 680 m³/h for fresh air in your kitchen.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 56 dB the hood is especially quiet when being used.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of product, without chimney (mm) : 323
 Minimum distance above an electric hob : 450
 Minimum distance above a gas hob : 600
 Net weight (kg) : 20.0
 Control panel : Electronic
 Max. air extraction (m³/h) : 420
 Boost position output recirculating (m³/h) : 570
 Max. recirculation (m³/h) : 380
 Boost position air extraction (m³/h) : 680
 Number of lights (Stck) : 2
 Noise level (dB) : 56
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable aluminium
 EAN code : 4242003761007
 Connection rating (W) : 263
 Current (A) : 10
 Nominal power (kW) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : GB plug
 Installation type : Wall-mounted



Optional accessories

LZ56200 : CleanAir active carbon filter spare part , LZ10AXL50 : Chimney extension 1500 mm , LZ10AXK50 : Chimney extension 1000 mm , LZ10AKU00 : Recirculation kit , LZ10AKT00 : Recirculation kit for chimless use , LZ10AKS00 : Recirculation kit regenerative , LZ10AKR00 : Recirculation kit regenerative chimless , LZ10AKA00 : Active carbon filter (spare part) , LZ00XXP00 : CleanAir act.carbon filter regenerative

iQ300
LC87KHM60B
Angled design
Chimney hood
Black
80 cm

Features	
Key performance features: • Energy Efficiency Class: A* • Extraction rate according to EN 61591 ø 15 cm: max. Normal use 420 m³/h Intensive 680 m³/h • Noise max. Normal Level: 56 dB* Features • 3 x power levels plus intensive setting • 2 x 3W LED • Colour Temperature: 3500 K • Twin channel high performance fan motor • Automatic intensive revert (6mins) • 2 x metal grease filter cassettes • easy to clean Inner frame • For wall mounted installation • Rim ventilation Design • Black glass Angled design • Chimney hood • Touch control for extractor speeds and light • Electronic control	Performance/technical information • Suitable for ducted and re-circulating operation • In recirculation operation chimless use possible • For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed • Easy installation system • Max. extraction rate: 680 m³/h • Extraction rate according to EN 61591 ø 15 cm: max. Normal use 420 m³/h Intensive 680 m³/h • Extraction rate in recirculation mode: Max. normal use: 380 m³/h Intensive: 570 m³/h • Noise max. Normal Level: 56 dB* • Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 56 dB(A) re 1 pW (42 dB(A) re 20 µPa sound pressure) Intensive: 65 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure) • Noise levels in recirculation mode: Max. normal use: 65 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure) Intensive: 75 dB(A) re 1 pW (61 dB(A) re 20 µPa sound pressure) • Power rating: 263 W • Light Intensity: 90 lux • Colour Temperature: 3500 K • Electrical cable length 1.3 m • Diameter pipe Ø 150 mm (Ø 120 mm enclosed) • Dimensions exhaust air (HxWxD): 928-1198 x 790 x 499 mm • Dimensions recirculating, chimney (HxWxD): 988-1258 x 790 x 499 mm • Dimensions recirculating, chimless (HxWxD): 452 mm x 790 x 499 mm • Dimensions recirculating with CleanAir module (HxWxD): 1118 x 790 x 499 mm - mounting with outer chimney 1188-1458 x 790 x 499 mm - mounting with telescopic chimney • Energy Efficiency Class: A* • Blower Efficiency Class: A* • Lighting Efficiency Class: A* • Grease Filtering Efficiency Class: C* • Average Energy Consumption: 51 kWh/year* Optional accessories • Recirculating kit <i>* In accordance with the EU-Regulation No 65/2014</i>

iQ300
LC87KHM60B
Angled design
Chimney hood
Black
80 cm

Dimensioned drawings

