

Serie | 6, Built-in double oven,
Stainless steel
MBA5350S0B



Included accessories

3 x combination grid
1 x universal pan

Optional accessories

HEZ327000 : Pizza stone
HEZ531000 : Baking tray, grey enamelled
HEZ531010 : Baking tray, non-stick ceramic coated
HEZ538000 : 1fold telescopic rail, level independent
HEZ634000 : Baking and roasting grid (standard)
HEZ638300 : 3 level telescopic rails, full ext
HEZ915003 : Glass roasting dish, 5,4 L

**The built-in double oven with AutoPilot:
automatically prepares perfect dishes.**

- **3D Hotair:** perfect results thanks to optimal distribution of heat on up to 3 levels simultaneously.
- **AutoPilot 10:** every dish is a perfect success thanks to 10 pre-set automatic programmes.
- **Pop-out controls:** for an easy to clean front.
- **EcoClean Direct:** almost no cleaning thanks to a special coating which covers interior walls and roof of the upper oven, the rear wall of the second oven

Technical Data

Color / Material Front :	Stainless steel
Construction type :	Built-in
Integrated Cleaning system :	No
Dimensions of the product (mm) :	888 x 594 x 550
Dimensions of the packed product (HxWxD) (mm) :	960 x 690 x 660
Control Panel Material :	Stainless steel
Door Material :	Glass
Net weight (kg) :	50.743
Usable volume of cavity (l) :	71
Cooking method :	
Conventional heat, Full width grill, Hot Air, Hot air grilling	
Oven control :	mechanical
Number of interior lights :	1
Approval certificates :	CE, VDE
EAN code :	4242005057610
Energy efficiency class (2010/30/EC) :	A
Energy consumption per cycle conventional (2010/30/EC) :	1.02
Energy consumption per cycle forced air convection (2010/30/EC) :	0.81
Energy efficiency class (2010/30/EC) - cavity 2 :	B
Energy consumption per cycle conventional - cavity 2 (2010/30/EC) :	0.83
Energy efficiency index (2010/30/EC) :	95.3
Energy efficiency index cavity 2 (2010/30/EC) :	120.3
Connection rating (W) :	5900
Current (A) :	32
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	fixed connection, no plug



Serie | 6, Built-in double oven, Stainless steel MBA5350S0B

The built-in double oven with AutoPilot: automatically prepares perfect dishes.

Design

- LCD-display control (white)
- Interior halogen light
- Rotary dial, Retractable control dials, round
- Straight bar handle

Features

- Control panel lock Residual heat indicator
- Electronic clock timer
- Automatic start Heating-up indicator AutoPilot

Top oven additional features

- Cavity volume: 34 litre capacity
- EcoClean Direct :ceiling, back panel, side liners
- Full glass inner door
- Door hinge small cavity: Drop down oven door
- Cavity (inner surface) top: Enamel grey

Top oven

- Oven with 4 heating methods: conventional top/bottom heat, Large-area grill, Small area grill, bottom heat
- Temperature range 50 °C - 275 °C

Main oven additional features

- Cavity volume: 71 litre capacity
- Door hinge big cavity: Drop down door
- Full glass inner door
- 5 shelf positions
- AutoPilot, 10
- Integral cooling fan

Main oven

- Oven with 5 heating methods: 3D Hotair, conventional top and bottom heat, Hotair grilling, full width variable grill, Hotair gentle
- Temperature range 50 °C - 275 °C
- Fast pre-heating function

Accessories

- 1 set of level independent telescopic rails, Stop function
- 1 x universal pan, 3 x combination grid

Performance/technical information

- Energy efficiency rating (acc. EU Nr. 65/2014): B (at a range of energy efficiency classes from A+++ to D) Energy consumption

per cycle in conventional mode: 0.83 kwh Number of cavities:

Top Cavity Heat source: electrical

- Energy efficiency rating (acc. EU Nr. 65/2014): B (at a range of energy efficiency classes from A+++ to D) Energy consumption per cycle in conventional mode: 0.83 kWh Energy consumption per cycle in fan-forced convection mode: 0.81 kwh Number of cavities: Main Cavity Heat source: electrical
- Total connected load electric: 5.9 KW
- Nominal voltage: 220 - 240 V
- Appliance dimension (hwxwd): 888 mm x 594 mm x 550 mm
- Niche dimension (hwxwd): 875 mm - 888 mm x 560 mm - 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual