

Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele					
Model name / identifier		DA 3366			
Annual Energy Consumption (AEC) (AEC_{Haube})		kWh/year	61,4		
Energy efficiency class					
Based on standard test results for 24 hours. Actual energy consumption will depend on how the appliance is used and where it is located.				C	
Energy efficiency index (EEI) (EEI_{Haube})			80,5		
Fluid Dynamic Efficiency (FDE) (FDE_{Haube})			14,2		
Fluid Dynamic Efficiency class					
A (most efficient) to G (least efficient)				D	
Lighting Efficiency (LE) (LE_{Haube})		lx/W	53,3		
Lighting Efficiency class					
A (most efficient) to G (least efficient)				A	
Grease Filtering Efficiency		%	89,0		
Grease Filtering Efficiency class					
A (most efficient) to G (least efficient)				B	
Airflow at best efficiency point		m ³ /h	246,8		
Air flow (min. speed)		m ³ /h	150		
Air flow (max. speed)		m ³ /h	320		
Air flow (intensive or boost setting)		m ³ /h	430		
Max. air flow (Q) (Q_{max})		m ³ /h	430		
Air pressure at best efficiency point		Pa	217		
Airborne acoustical A-weighted sound power emissions (min. speed)		dB	44		
Airborne acoustical A-weighted sound power emissions (max. speed)		dB	51		
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)		dB	58		
Electrical power input at best efficiency point		W	105,0		
Power consumption in off mode (P_o)		W	0,00		
Power consumption in standby mode (P_s)		W			
Nominal power of lighting system		W	6,0		
Average illumination of the lighting system on the cooking surface		lx	320		
Time increase factor			1,5		