Data sheet for household cooker hoods
In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele				
Model name / identifier		DA 3566		
Annual Energy Consumption (AEC)				
(AEC _{Haube})	kWh/year	31,5		
Energy efficiency class				
Based on standard test results for 24 hours. Actual en	nergy			
consumption will depend on how the appliance is used				
it is located.		A+		
Energy efficiency index (EEI)				
(EEI _{Haube})		41,5		
Fluid Dynamic Efficiency (FDE) (FDE _{Haube})		36,8		
Fluid Dynamic Efficiency class				
A (most efficient) to G (least efficient)		Α		
Lighting Efficiency (LE) (LE _{Haube})	lx/W	46,7		
Lighting Efficiency class				
A (most efficient) to G (least efficient)		A		
Grease Filtering Efficiency	%	82,8		
Grease Filtering Efficiency class		0		
A (most efficient) to G (least efficient)	3	С		
Airflow at best efficiency point	m³/h	333,0		
Air flow (min. speed)	m³/h	220		
Air flow (max. speed)	m³/h	400		
Air flow (intensive or boost setting)	m³/h	640		
Max. air flow (Q) (Q _{max})	m³/h	640		
Air pressure at best efficiency point	Pa	402		
Airborne acoustical A-weighted sound power emission	ns			
(min. speed)	dB	39		
Airborne acoustical A-weighted sound power emission				
(max. speed)	dB	51		
Airborne acoustical A-weighted sound power emission				
(intensive or boost setting)	dB	63		
Electrical power input at best efficiency point	W	101,0		
Power consumption in off mode (P _o)	W			
Power consumption in standby mode (Ps)	W	0,15		
Nominal power of lighting system	W	9,0		
Average illumination of the lighting system on the cool		400		
surface Time increase factor	lx	420 0,7		
Time increase factor		U, /	 	