

Serie | 8 Hoods

60 cm wide Telescopic hood
DFS067J50B Brushed steel



Telescopic cooker hoods extend when in use and slide neatly away when not in operation.

- An impressive extraction rate of 700 m3/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.
- **Especially quiet:** high performance at just 40 dB.

Technical Data

Typology :	Pull-out
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	175
Required niche size for installation (HxWxD) :	385mm x 524mm x 290mm
Minimum distance above an electric hob :	430
Minimum distance above a gas hob :	650
Net weight (kg) :	12.0
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m3/h) :	400
Boost position output recirculating (m3/h) :	480
Maximum output recirculating air (m3/h) :	290
Boost position air extraction (m³/h) :	700
Number of lights (Stck) :	2
Noise level (dB) :	54
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable stainless steel
EAN code :	4242002918952
Connection rating (W) :	146
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Built-in



Optional accessories

- DSZ4561 : Active carbon filter
- DSZ4565 : Recirculating kit
- DSZ4680 : CleanAir Recirculation Kit
- DSZ4681 : CleanAir active carbon filter

Serie | 8 Hoods

60 cm wide Telescopic hood DFS067J50B Brushed steel

Telescopic cooker hoods extend when in use and slide neatly away when not in operation.

Key features

- Electronic control via TouchControl
- Efficient BLDC technology

Design

- 60 cm wide
- Brushed steel
- Telescopic hood
- Stainless steel and black fascia panel with Bosch logo
- For installation into a 60cm wide cupboard

Features

- TouchControl with lightline
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- Automatic after running (10 min)
- Additional noise reduction insulation
- Silence kit
- 2 x LED lights
- Softlight dimmer function
- Dimmer function
- Neutral white lights
-
- 2 removable metal grease filter cassettes
- Removable metal grease filters

Performance/technical information

- Telescopic easy installation
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 400 m³/h
Intensive 700 m³/h
- Extraction rate exhaust air according to EN 61591:
max. normal use 400 m³/h, intensive 700 m³/h
- Power rating: 146 W
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 54 dB(A) re 1 pW (40 dB(A) re 20 µPa sound pressure)
Intensive: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
- Noise max. Normal Level: 54 dB*
- Average Energy Consumption: 34.1 kWh/year*
- Energy Efficiency Class: A*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Dimensions (HxWxD): 426 x 598 x 290 mm
- Dimensions exhaust air (HxWxD): 426-426 x 598 x 290 mm
- Dimensions recirculating (HxWxD): 426-426 x 598 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Light Intensity: 683 lux
- Colour Temperature: 3500 K

Optional accessories

- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed

Serie | 8 Hoods

60 cm wide Telescopic hood DFS067J50B Brushed steel

