

Serie | 2 Hoods

Integrated extractor hood
DHE645MGB Silver metallic
lacquer



Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

- An impressive extraction rate of 370 m3/h ensures this hood will have your kitchen odour free in no time.

Technical Data

Typology :	Pull-out
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Minimum distance above an electric hob :	650
Minimum distance above a gas hob :	650
Net weight (kg) :	9.0
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m3/h) :	270
Maximum output recirculating air (m3/h) :	300
Number of lights (Stck) :	2
Noise level (dB) :	63
Diameter of air outlet (mm) :	120
Grease filter material :	Washable aluminium
EAN code :	4242002253954
Connection rating (W) :	270
Voltage (V) :	220-230
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Wall-mounted



Optional accessories

DSZ11AF : Charcoal filter for recirculation oper.

Serie | 2 Hoods

Integrated extractor hood

DHE645MGB Silver metallic lacquer

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

Design

- 60 cm wide
- For installation between cupboards

Features

- Rocker switch control
- 3 power levels
- 2 x 40W Light
- 2 removable metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591: max. 370 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 63 dB(A) re 1 pW (49 dB(A) re 20 µPa sound pressure)

Optional accessories

- Charcoal odour filter DSZ11AF

DHE645MGB Silver metallic lacquer



Measurements in mm



Measurements in mm



Measurements in mm