

Serie | 6 Hoods
**Exxcel
island chimney hood with
glass canopy
DIA098E50B brushed steel**
A+

Stylish island chimney hoods perfectly complement island hob installations.

- An impressive extraction rate of 790 m³/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	699-879/699-999
Height of product, without chimney (mm) :	52
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	32.0
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	430
Boost position output recirculating (m ³ /h) :	360
Maximum output recirculating air (m ³ /h) :	290
Boost position air extraction (m ³ /h) :	790
Number of lights (Stck) :	4
Noise level (dB) :	58
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002775937
Connection rating (W) :	172
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Island


Optional accessories

DHZ5365 : Recirculating kit

Serie | 6 Hoods

Exxcel **island chimney hood with glass canopy** **DIA098E50B brushed steel**

Stylish island chimney hoods perfectly complement island hob installations.

Key features

- Electronic control
- Electronic power level display
- Grease and charcoal filter saturation indicators

Design

- 90 cm wide
- Designed for ceiling mounted installation
- Height adjustable chimney sections
- brushed steel with glass canopy

Features

- Soft touch button control for extractor speeds and light
- 4 x 20 W
- Automatic intensive revert
- Softlight dimmer function
- Florescent mood lighting
- 2 removable metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 430 m³/h
Intensive 790 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20 µPa sound pressure)
- Maximum extraction rate 790 m³/h (intensive)
- Extractor hose 120mm

Optional accessory

- Recirculating kit DHZ5365

Serie | 6 Hoods

Exxcel

island chimney hood with glass canopy DIA098E50B brushed steel

