

**iQ100**  
**LC64BBC50B**  
**Box design**  
**Chimney hood**  
**Stainless Steel**  
**60 cm**

D



Box design extractor hood with high extraction rate.

- ✓ The motor with a high extraction rate of 340 m³/h for fresh air in your kitchen.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ At 63 dB the hood is especially quiet when being used.

## Features

### Technical Data

Color chimney : Stainless steel  
 Typology : Chimney  
 Approval certificates : CE, G-Mark, VDE  
 Length of electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 583-912/583-1022  
 Height of product, without chimney (mm) : 53  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 11.135  
 Control panel : mechanical  
 Number of speed settings : 3  
 Max. air extraction (m³/h) : 340  
 Max. recirculation (m³/h) : 190  
 Number of lights (Stck) : 2  
 Noise level (dB) : 63  
 Diameter of air outlet (mm) : 150 / 120  
 Grease filter material : Washable aluminium  
 EAN code : 4242003811047  
 Connection rating (W) : 100  
 Current (A) : 10  
 Nominal power (kW) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : GB plug  
 Installation type : Wall-mounted



## Optional accessories

LZ57000	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ50661	Backboard 60 x 72 cm
LZ50660	Backboard 60 x 65 cm
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ10FXI00	Integrated CleanAir Recirculation Kit
LZ10DXU00	Recirculating kit
LZ10DXA00	Active carbon filter
LZ00XPP00	CleanAir act.carbon filter regenerative

**iQ100**  
**LC64BBC50B**  
**Box design**  
**Chimney hood**  
**Stainless Steel**  
**60 cm**

#### Features

##### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A++ to E)\*
- Max. extraction rate: 340 m<sup>3</sup>/h
- Noise max. Normal Level: 63 dB\*

##### Features

- Push button control for extractor speeds and light
- 3 x power levels
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- 2 x metal grease filter cassettes
- For wall mounted installation

##### Design

- Box design
- Chimney hood
- Mechanical

##### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 340 m<sup>3</sup>/h
- Maximum extraction rate exhaust air 340 m<sup>3</sup>/h according to EN 61591
- Extraction rate in recirculation mode:
- Max. normal use: 190 m<sup>3</sup>/h
- Noise max. Normal Level: 63 dB\*
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 63 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
- Noise level in recirculation mode:
- Max. normal use: 66 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Power rating: 100 W
- Light Intensity: 99 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 635-1075 x 600 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 703 x 600 x 500 mm - mounting with outer chimney
- 833-1163 x 600 x 500 mm - mounting with telescopic chimney
- Energy Efficiency Class: D (at a range of energy efficiency classes from A++ to E)\*
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 53.2 kWh/year\*

##### Optional accessories

- Recirculating kit

\* In accordance with the EU-Regulation No 65/2014

**iQ100**  
**LC64BBC50B**  
**Box design**  
**Chimney hood**  
**Stainless Steel**  
**60 cm**

## Dimensioned drawings

