

Serie | 6 Hobs

PPP6A6B90
60 cm hob, Tempered glass,
Black



The tempered-glass gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- **FlameSelect:** for a precise adjustment of the flame in nine defined levels.
- **Standard and semi-flush built-in option:** choose between flush or surface mounted installation.
- **Tempered-glass surface:** elegant design and easy cleaning.
- **Continuous cast-iron pan support:** for high firmness and stability of cookware.
- **Sword knobs:** for an ergonomic control.

Technical Data

| | |
|---|-------------------------------|
| Product name/family : | gas hob w integrated controls |
| Installation type : | Built-in |
| Heating type : | Gas |
| Total number of positions that can be used at the same time : | 4 |
| Required niche size for installation (HxWxD) : | 45 x 560-562 x 480-492 |
| Width (mm) : | 590 |
| Dimensions of the product (mm) : | 45 x 590 x 520 |
| Net weight (kg) : | 13.0 |
| Gross weight (kg) : | 14.0 |
| Residual heat indicator : | without |
| Location of control panel : | Hob front |
| Basic surface material : | Hard glass |
| Color of surface : | Black |
| Color of frame : | Black |
| Approval certificates : | CE |
| Length of electrical supply cord (cm) : | 100 |
| EAN code : | 4242002801933 |
| Gas connection rating (W) : | 7500 |
| Current (A) : | 3 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 50; 60 |



4 242002 801933

Serie | 6 Hobs

PPP6A6B90

60 cm hob, Tempered glass, Black

The tempered-glass gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

Design

- Tempered glass Black
- frameless design

Special features

- FlameSelect
- Design co-ordinated control dials
- Ignition via control dials
- Cast iron pan supports with rubber feet

Power and size:

- 4 gas burners:
- Left rear: Standard burner 1.75 KW
- Right rear: high-speed burner 3 KW
- Left front: standard burner 1.75 KW
- Right front: economy burner 1 KW

Safety Features

- Flame failure safety device
- Pre-set for natural gas

Technical information

- Power cord length 100 cm

Accessories

- LPG jets included. Connection to 28-30/37 mbar bottled gas

